Vol. 14, No. 1-4, 2001.



International Journal for

ENGINEERING MODELLING

UDC 62 519 681.3.06 ISSN 1330 1365

Publishers: FACULTY OF CIVIL ENGINEERING, UNIVERSITY OF SPLIT FACULTY OF CIVIL ENGINEERING, UNIVERSITY OF ZAGREB ENGINEERING MODELLING CENTER, UNIVERSITY OF SPLIT

INT. J. ENG. MODEL., YEAR XIV,

R XIV, NUM

NUMBER 1-4,

PAGES 1-90,

SPLIT 2001.

International Journal for

ENGINEERING MODELLING

ADVISORY BOARD

VINKO JOVIĆ

Faculty of Civil Engineering, University of Split, HR-21000 SPLIT, Matice hrvatske 15, Croatia

JURE RADIĆ

deputy editor-in-chief. Faculty of Civil Engineering, University of Zagreb, HR-10000 ZAGREB, Fra Andrije Kačića Miošića 26. Croatia

EDITORIAL BOARD

IVO ALFIREVIĆ

Faculty of Mechanical Engineering and Naval Architecture, University of Zagreb, HR-10000 ZAGREB, Ivana Lučića 5, Croatia

BLAŽ GOTOVAC

Faculty of Civil Engineering, University of Split, HR-21000 SPLIT, Matice hrvatske 15, Croatia

DIMITAR JURUKOVSKI

Institute for Earthquake Eng. and Engineering Seismology, 91000 SKOPJE, Pat Skopje Vodno, p.p. 101, Macedonia

GEORGE MANOS Aristotele University of Thessaloniki Department of Civil Engineering, GR - 54006 THESSALONIKI, Greece

JOŠKO OŽBOLT Institut für Werkstoffe im Bauwesen, Universität Stuttgart, D-7000 STUTTGART,

Deutschland LEOPOLD ŠKERGET

University of Maribor, Technical Faculty, SI-2000 MARIBOR, Smetanova 17, Slovenia

MEHMED ČAUŠEVIĆ Faculty of Civil Engineering, University of Rijeka, HR-51000

RIJEKA, V. Cara Emina 5,

Croatia

ZIJAD HAZNADAR Faculty of Electrical Engineering and Computing, University of Zagreb, HR-10000 ZAGREB, Unska 3, Croatia

MATE KURTOVIĆ Faculty of Electrical Engineering, Mechanical Engineering and Naval Architecture, University of Split, HR-21000 SPLIT, Rudera Boškovića b.b., Croatia

KEN MORGAN University College of Swansea, Singleton Park, SWANSEA, SA2 8PP, Wales, United Kingdom

BERNARD SCHREFLER Universitá degli Studi di Padova, Instituto di Scienza e Technica delle Costruzioni, I-35131 PADOVA, Italia

BORIS ŠTOK

University of Ljubljana, Faculty of Mechanical Engineering, SI-1000 LJUBLJANA, Aškerčeva 6, Slovenia

EDITOR-IN-CHIEF ANTE MIHANOVIĆ

EDITOR PAVAO MAROVIĆ

Faculty of Civil Engineering, University of Split, HR-21000 SPLIT, Matice hrvatske 15, CROATIA

TECHNICAL EDITOR

BORIS TROGRLIĆ

Faculty of Civil Engineering, University of Split, HR-21000 SPLIT, Matice hrvatske 15, Croatia

PETER FAJFAR

IKPIR & Faculty of Civil Engineering and Surveying, University of Ljubljana, SI-1000 LJUBLIANA, Jamova 2, Slovenia

VESNA JURČEC National Meteorological and Hydrological Department, HR-10000 ZAGREB, Grič 3, Croatia

HERBERT MANG Institut für Festigkeitslehre, Technische Universitaet Wien, Karlsplatz 13 / 202. A-1040 WIEN, Osterreich

D. ROGER J. OWEN

University College of Swansea, Singleton Park, SWANSEA, SA2 8PP, Wales, United Kingdom

BENSON SHING Engineering Centre OT4/02, Campus Box 428, University of Colorado, BOULDER, Colorado 80309/0428, U.S.A.

ZVONIMIR ŽAGAR Faculty of Civil Engineering, University of Zagreb, HR-10000 ZAGREB, Fra Andrije Kačića

The papers from this journal are cited/indexed in the next Abstract Journals or Data bases:

CITIS International Civil Engineering Abstracts, Dublin, Ireland; INSPEC The Database for Physics Electronics and Computing, U.K.; ENGINEERING INFORMATION INC., Hoboken, U.S.A.; BULLETIN SCIENTIFIQUE, Zagreb, Croatia; CEIA Civil Engineering Institute Abstracts, Zagreb, Croatia; Geomechanics Abstacts, GEOBASE, Fluid Abstracts: Civil Engineering, FLUIDEX, Elsevier Science, Oxford, England, U.K.

Printed by: Typo, Čišla

Printed in December 2002

Circulation: 250 issues

The editing of this Journal has been partly supported by the Ministry of Science and Technology of the Republic of Croatia.

ANTUN SZAVITS-NOSSAN Faculty of Civil Engineering, University of Zagreb HR-10000 ZAGREB, Fra Andrije

JOSIP DVORNIK

Kačića Miošića 26, Croatia

Faculty of Civil Engineering. University of Zagreb, HR-10000 ZAGREB, Fra Andrije Kačića Miošića 26, Croatia

IBRAHIMBEGOVIĆ Technologie, Secteur Genie Civil, (ENS Cachan/CNRS/Univ. Paris 6)

ŽELJAN LOZINA Faculty of Electrical Engineering, Mechanical Engineering and Naval Architecture, University of Split, HR-21000 SPLIT, Rudera Boškovića b.b., Croatia

ANTE MUNJIZA University of London, QMW Department of Engineering, Mile End Road, LONDON, E1 4NS, England, United Kingdom

IVO SENJANOVIĆ Faculty of Mechanical Engineering and Naval Architecture, University of Zagreb, HR-10000 ZAGREB,

KUMAR K. TAMMA University of Minnesota, Dept. of Mechanical Engineering, 111 Church St. S.E., MINNEAPOLIS, Minnesota 55455, U.S.A.

ADNAN

Laboratoire de Mecanique et F - 94235 CACHAN Cedex, France

Ivana Lučića 5. Croatia

Miošića 26, Croatia

International Journal for

ENGINEERING MODELLING

Vol. 14, No. 1-4, 2001.

Contents

A simple model f Jednostavan model	or chaos studi za proučavanje	es in nonlinear fee e kaosa kod nelinear	e dback systems nih sustava s		
povratnom vezom A. Ucar	- /			(original scientific paper)	1
CMAC neural net control of a redu Metoda CMAC neur redundantnog man Y. Li and S.H. Leon	work method ndant manipu ralne mreže i pr ipulatora g	with application to lator imjena na kinematič) kinematics ku kontrolu	(original scientific paper)	7
Nonlinear model identification Nelinearno modelin	ling of MCFC s ranje MCFC sku	stack based on RBF pa zasnovanog na id	ncural networks entifikaciji RBF		
Ch. Shen, GY. Cae	o and XJ. Zhu			(original scientific paper)	15
Numerical model Numeričko modeli L. Frgić, K. Tor and	ling of rock p ranje plastičnog A. Jaguljnjak-La	lastic yielding popuštanja stijensko azarević	og masiva	(original scientific paper)	21
Seismic damage r Model siezmičke os D. Morić, M. Hadzin	nodel for regu sjetljivosti za pra ma and D. Ivan	ilar structures avilne konstrukcije ušić		(original scientific paper)	29
Bearing capacity Spektri dijagrama n A. Jurić and A. Miha	spectra for ste osivosti čeličnil 1nović	e ci structures 1 konstrukcija		(original scientific paper)	45
Visualization of t Vizualizacija proces T. Tomiša, I. Kuzle	he cruđe oil m sa topljenja tešk and S. Tešnjak	<mark>telting process</mark> ih derivata		(original scientific paper)	55
Monitoring to eva	uluate blasting	quality and the p	ediction of		
Monitoring za proc B. Božić	jenu kvalitete m	niniranja i za predviđ	anje fragmentacije	(original scientific paper)	61
				(continued c	on next page
Publishers: Address: Broj žiro računa: Account No.: Obavijest o pretplati:	Faculty of vis d En Engineering Mode Faculty of Civil En 🕿 + (385) (21) 30, 34400-603 (6371, a Privredna Banka 2 Za Hrvatsku: Indiv	gineering University of S ₁ Iling Center University of gineering University of S ₁ 3–334 or 303-352; Fax. + (s naznakom "za časopis I. zagreb PJ Split, Croatia, 20 'idualna pretplata 60 kn; b	lit, Faculty of Civil Engineerir Split lit, Matice hrvatske 15, HR-21 385) (21) 465-117; E-mail: en M." (samo za Hrvatsku). -188-92215-7 (payable to P. M olektivna pretplata 250 kn.	ng University of Zagreb, 000 Split, Croatia gmod@gradst.hr farovič).	
Subscription rate: The editing	ror Europe 410 Eu 3 of this Journal has	iros; for Slovenia, Bosnia Journal i been partly supported b	ind Herzegovina and Macede i published quarterly y the Ministry of Science and	min 55 Euros; for oversets countries Technology of the Republic of Cro	ata.
UDC 62 . [519 - 68	1. 3. 06]			IS	SN 1330-136
ENGINEERING MC	DDELLING	YEAR XIV	NUMBER 1-1	PAGES 1-90	SPLIT 2001

Visualization of the crude oil melting process

Tomislav Tomiša, Igor Kuzle and Sejid Tešnjak

Faculty of Electrical Engineering and Computing, Department of Power Systems, University of Zagreb, Unska 3, HR-10000 Zagreb, CROATIA e-mail: tomislav.tomisa@zvne.fer.hr; igor.kuzle@zvne.fer.hr; sejid.tesnjak@zvne.fer.hr

SUMMARY

An experiment in real condition was performed to support the development of a new designed crude oil pumping facility on the tank wagon decanting station. Since the pumping process failed during the previous tests, the visualization of the heating process inside the tank was required to find out the optimized parameters for the improved automatic pumping algorithm. The 32 temperature sensors were installed inside the tank wagon before loading with oil, and connected to the PC based data acquisition system. The measured data collected during the whole heating/pumping process were graphically presented to visualize the time depended 3-dimensional oil temperature distribution inside the tank. Finally, the successful reconstruction of pumping facility was made based on those results.

Key words: heating process of crude oil, tank wagon, temperature field, data acquisition, process visualization.

1. INTRODUCTION

1

At the ambient temperature below zero degree a crude oil becomes solid. Since even at the normal ambient temperature the crude oil is in gel condition. it has to be preheated at least up to 45°C to melt it before pumping. Once loaded, wagon tank can be discharged at the destination only after the whole content is melted performing appropriate heating procedure.

Generally there are two principles for crude oil melting before decanting the tank wagon:

- indirect heating the tank is heated from outside using a hot water or hot air until the tank content becomes enough liquid to be emptied trough a drain pipe,
- direct heating the tank content is heated from inside using a special heating body which penetrates into the oil through the upper hatch of the wagon and it pumps-out the melted content.

Since the indirect heating cannot be performed in the open area (it requires a large closed and heated room) the direct heating method has an advantage because it requires significantly less energy consumption for oil melting, but it uses much more

complex decanting equipment. The experimental prototype of such decanting facility consists of the following subsystems (Figure 1):

- mechanical arm (motor-controlled in three axes) carrying the dip-in heating body including the suckin and sprinkling pipes,
- pumping subsystem including the steam heat exchanger provided with the appropriate control valves,
- control cabinet with the PLC-based process control unit.

DECANTING FACILITIES





The oil heating process is realized in three phases: pre-heating, circulation and decanting using specially developed heating/pumping facility mentioned above. During the pre-heating phase a certain amount of the oil around the dip-in heater in the tank wagon should be melted to enable oil circulation.

In the second phase oil is pumped out and heated in temperature controlled heat exchanger up to $80^{\circ}C$. Such heated oil is returned back into the tank wagon using sprinklers which will melt the rest of the unmelted oil. The circulation is performed until the total content of the tank is heated up to $45^{\circ}C$. Finally, the melted oil is pumped out during the third phase (decanting).

2. EXPERIMENT

Since the complete heating process has to be performed automatically controlled by PLC unit, the appropriate relations between the time duration and oil temperature for each phase should be obtained from the experiment to parameterize the PLC program.

The essential problem is to determine the appropriate time duration of pre-heating phase. If the chosen time is too short the circulation process cannot start successfully, while if the pre-heating duration was too long the whole decanting process cannot be ended in a disposable time period.

The successful start of the circulation pump depends on the amount of the melted oil that should be enough to fill the complete circulation pipe system without air.

The duration times of the pre-heating (T_I) , circulation (T_2) and pumping (T_3) phases are the parameters which have to be determined depending on the outside temperature, starting oil temperature and the thermal characteristics of the oil.

A total process time is limited with decanting schedule time T_{max} :

$$T_{iot} = T_1 + T_2 + T_3 < T_{max}$$
(1)

The pre-heating time T_I depends on:

- thermal characteristics of the oil,
- starting oil temperature (ϑ_0),
- power of dip-in heating body (P_1) ,
- heat transfer conditions around heating body.

The circulation time T_2 is determined by the sprinkling subsystem characteristics (pressure, temperature) but it also depends on the initial oil temperature and thermal characteristics, tank volume and temperature required for pumping.

As mentioned before, to ensure successful start of circulation, a certain amount of oil volume (V_i) have to be pre-heated at the temperature (ϑ_i) using heat quantity:

$$Q_I = m_I \cdot c_p \cdot \Delta \vartheta \tag{2}$$

where: m_I stands for mass of pre-heated oil $(V_I \cdot \rho) [kg]$; c_ρ is specific heat $[kJ/kg^\circ C]$; $A\vartheta$ stands for temperature difference $(\vartheta_1 \cdot \vartheta_0) [\uparrow^\circ C]$.

Since the total input heat, during the pre-heating phase, is given by:

$$Q_I = P_I \cdot T_I \tag{3}$$

the pre-heating time can be expressed as:

$$T_{I} = \frac{Q_{I}}{P_{I}} = \frac{V_{I} \cdot \rho \cdot c_{\rho} (\vartheta_{I} - \vartheta_{2})}{P_{I}}$$
(4)

It can be seen that duration of the pre-heating time, taking into account given conditions, is determined by the volume V_i that generally is not known. This is the reason why the experiments in the real conditions are performed to estimate a minimal duration of the pre-heating time which for given conditions ensure the successful start of the circulation phase.

The circulation time T_2 depends on the rated values of the pumping subsystem (heating power, pump capacity), as well as on the oil thermal characteristic and the total tank volume.

The pumping time T_3 is determined with the pump rated capacity and depends on total tank volume.

3. EXPERIMENT DESIGN

The basic task of the experiment was to find out the oil temperature distribution inside the tank during the heating process. The tank wagon of $37 m^3$ capacity $(\Phi 2.8 \times 6 m)$ was used for the experiment.

The characteristics of the prototype plant are: preheater power $P_1=21 \ kW$, tank volume $V=37 \ m^3$, low pumping temperature $45^{\circ}C$, heated oil output temperature $100^{\circ}C$.

For oil temperature measurement at the certain positions, 29 temperature sensors are placed inside the tank before oil loading, as shown in Figure 2.



Fig. 2 Temperature sensors positions

Since the tank is symmetrical, only one quarter of the tank was provided with the sensors that are installed using a special mounting construction in three vertical cross-section planes of the tank (Figure 3):

- cross-section A-A: at the distance of 0.5 m from the center of the tank,
- cross-section B-B: at the distance of 1.5 m from the center of the tank,
- cross-section C-C: at the distance of 2.5 *m* from the center of the tank.



Fig. 3 Sensors positions in vertical cross-section planes of the tank

In each cross-section 9 sensors are placed in two axes:

- vertical axis: 6 sensors at intervals of 0.4 m
- horizontal axis: 3 sensors at intervals of 0.4 m

Between each cross-sections 2 sensors are placed in the central axis at the distance of 1.0 m and 2.0 mfrom the center of the tank. One movable sensor is placed near the inlet of the suck-in pipe in the tank.

Additionally, the outside tank temperature was measured using the sensor placed on the outside tank surface.

Specially designed 32-channel data acquisition system is used to collect temperature data during the heating process (Figure 1). The data are sampled continuously, but mean values are calculated every minute and stored in the file for post processing. The values of the actual pump current and rotating speed, input pressure and heated oil output temperature are also collected at certain periods of interest with the sampling rate of 50 ms for the analysis purposes.

4. RESULTS OF EXPERIMENT AND PROCESS VISUALIZATION

The time-temperature profiles are plotted using data recorded during the progress of the experiments. The conditions before the start of the pre/heating phase were:

-	outside	temperature	$0 \ ^{\circ}C$
---	---------	-------------	-----------------

- mean oil temperature $< 45 \ ^{\circ}C$

and the progress of the described experiment was as follows:

- pre-heating start time: $10:40 h T_1=0$ - duration of pre-heating up to: $12:24 h T_1=1h 44 min$

- circulation start time:

12:24 h UNSUCCESSFUL

- prolongation of pre-heating up to: $13:00 h = T_1 = 2h \ 20 min$

- retry of circulation at:
- 13:00 h

- circulation up to:

15:24 h $T_2=1h 36 min$ Total experiment duration: 4h 44 min.

SUCCESSFUL

The time various temperature fields inside the tank is constructed on the basis of the recorded data. Since only one quarter of the tank volume was covered with placed sensors, the corresponded data are mirrored to obtain an image of the whole tank volume. Such arranged data are used to obtain the isothermal lines in the corresponded horizontal and vertical planes.

The calculation is made using sophisticated Kirighin algorithm on electronic computer (PC). These calculated data are used as input data for a volumetric time various temperature field reconstruction. An example of the measured temperature field (at the start of the experiment, at the beginning of the circulation and at the end of the experiment) through the vertical cross-section of the tank is shown on Figure 4.

From already calculated temperature field inside the tank it is possible to calculate volume of the given oil temperature at every time instant (Figure 5).

5. MODELING OF HEATING PROCESS

A heating process model is based on the energetic calculations (source for physical characteristics of crude oil was GOST standard 10585-75). As the range of an interest was the temperature region ($0-100^{\circ}C$), the mean values are used: specific heat of oil ($c_p=1.95 \text{ kJ/kgK}^{\circ}C$) and a specific density of oil ($p=900 \text{ kg/m}^3$).

The initial conditions for the described experiment (before taking a pre-heater in the tank) are calculated from the measured data using the mentioned temperature field reconstruction algorithm:

- mean temperature of a cold oil envelope:
- $\vartheta_h = 20^{\circ}C$ (70 % of oil volume),
- mean temperature of a warm oil substance: $\vartheta_t = 27^\circ C (30\% \text{ of oil volume}),$
- mean temperature of the total oil volume: $\vartheta_0 = (20.0.7 + 27.0.3) = 22^{\circ}C.$

The minimal duration of the pre-heating phase which ensures a successful circulation after the cold start ($\vartheta_s < 45^{\circ}C$), as derived from performed experiments, should be $T_I = 2.5 h$, with input heat amount of $W_I = 189 \text{ MJ}$. From the reconstructed temperature field, the mass of the oil heated above $45^{\circ}C$ after 2.5 h is: $m_I = V_{45}\rho = 5.8\cdot900 = 5220 \text{ kg}$. Since the pre-heating influences only a warm oil substance, the required heat amount to warm the mass m_I from 27°C to 45°C is: $Q_I = m_I c_p(\vartheta_I - \vartheta_I) = 5220 \cdot 1.95 \cdot (45-27) = 183 MJ$. This is well corresponded with the amount of the input heat W_I (189 MJ).



- \bigcirc $T_I=60 min$
- d) $T_I = 120 \min$
- c) $T_I = 180 \min_{f_1} T_I = 270 \min_{f_1}$

Fig. 4 Temperature field inside the tank





Using temperature field reconstruction algorithm, the volumes of oil heated above 45 $^{\circ}C$ are calculated at the certain time instants:

- at the beginning of the circulation: $V_{45(t=2.5h)}=5.8 m^3$
- after 30 min. of proceeded circulation: V_{45(1=3.0h)}=13.9 m³
 after 90 min. of proceeded circulation:
- after 90 min. of proceeded circulation: $V_{45(1=4.0h)}=19.4 \text{ m}^3$

The mean temperatures of these volumes are determined by correspondent time-temperature profiles:

- at the beginning of the circulation: $\vartheta_{s(t=2.5h)} = 45^{\circ}C$
- after 30 min. of proceeded circulation: $\vartheta_{s(t=3.0h)}=55^{\circ}C$
- after 90 min. of proceeded circulation: $\vartheta_{s(t=4.0h)} = 74^{\circ}C$

The calculations of required heat are:

* after 30 min. heated volume of 13.9 m³ occupies practically only initial oil warm substance (about 30% of tank volume). Assuming a very low thermal conductance of the oil, there will be no changes in the oil temperature, ($\vartheta_t = 27^{\circ}C$), outside this heated volume, so:

$$Q_{30} = V_{45(t=2.5h)} \cdot \rho \cdot c_p \left[\vartheta_{s(t=3.0h)} - \vartheta_{s(t=2.5h)} \right] + \left[V_{45(t=3.0h)} - V_{45(t=2.5h)} \right] \cdot \rho \cdot c_p \left[\vartheta_{s(t=3.0h)} - \vartheta_t \right] = 500 \text{ MJ}$$

and the calculated mean heating power:

$$P_2 = \frac{Q_{30}}{0.5h} = 278 \ kW$$

* after 90 min. heated volume of 19.4 m³ occupies particularly initial cold oil envelope. Assuming a very low thermal conductance of the oil, there will be no changes in oil temperature ($\vartheta_h = 20^{\circ}C$), outside this heated volume, so $Q_{90}=984$ MJ and the calculated mean heating power is:

$$P_2 = \frac{Q_{90}}{lh} = 273 \, kW$$

The comparison of the calculated mean heating power confirms heating energy balance i.e. reconstructed temperature fields. Next calculation will be made using mean heating power value: $P_2=275 kW$. Since heated oil output temperature is $\vartheta_i=100^{\circ}C$, this is also a theoretical value which could be achieved inside the tank neglecting cooling losses. Recorded time-temperature profile can be approximated, assuming an exponential law of temperature rise in oil warm substance, as:

$$\vartheta_{s} = \vartheta_{i} - \left[\vartheta_{i} - \vartheta_{s(i+2.5h)} \right] \cdot e^{-\theta_{s} t_{i}} = 100 - 55e^{-\theta_{s} t_{i}}$$
(5)

where t_r is heating time in circulation mode (hours).

A total time from the start of the experiment is then $t=T_1+t_r$. After 90 min, of heating (t=2.5+1.5=4 h) in

tank there is 19.4 m^3 heated oil of mean temperature 74°C and 17.6 m^3 oil of mean temperature 20°C (rest of a cold envelope). Let's make prediction using exponential law - in next 90 min. of heating $(t_r=3 h)$ the mean oil temperature will raise up to 88 °C. During 90 min. of circulation the energy brought into the tank is $W=P_2\cdot 1.5 h=275 kW\cdot 1.5 h=1485 MJ$, consisting of 476 MJ used for warm oil substance heating and 1009 MJ used for cold oil envelope heating. The cold oil envelope then achieves the temperature of 53°C at which oil viscosity satisfies pumping conditions.

6. CONCLUSION

In order to heat the tank oil contents up to the required temperature, total circulation time should be $T_2=180 \text{ min}=3 \text{ h}$ which gives the total heating time of 5.5 h (pre-heating $T_1=2.5 \text{ h}+\text{circulation } T_2=3.0 \text{ h}$). Since the process control is based only on the predefined duration of the pre-heating and circulation times, as functions of initial oil temperature (no information are returned from the tank), a change of the pump input pressure should be used as the measure of the circulation set-up efficiency.

7. REFERENCES

- Heavy Oil Decanting Station Prototype, P&I Diagrams, INA-ROSS, Zagreb, 1995.
- [2] Petrol Plant GRUŠOVAJA Novosibirsk, Project No. M-50-92, INA-ROSS, Zagreb, 1992.
- [3] MATRIXX/PC, Digital Signall Processing Module, Ver. 8.0, Integrated Systems Inc., 1990.
- [4] SURFER Access System, Ver. 3.0, Golden Software, 1987.
- [5] Energy-saving Activities by Improving Melting Method of Ductile Segment Casting Line, TSY Circle, Manufacturing Section No. 1, Onkajima Plant, Kubota Ltd., The Energy Conservation Center (ECC), Japan, 1998.

VIZUALIZACIJA PROCESA TOPLJENJA TEŠKIH DERIVATA

SAŽETAK

Proces pretakanja teških derivata (mazuta) iz cisterne u neposrednoj je vezi sa zagrijavanjem i pumpanjem. U tu se svrhu koriste posebna postrojenja, obično automatski upravljana. U radu je razrađen i opisan proces zagrijavanja i pretakanja na način da isti može biti automatski vođen programibilnim logičkim automatom (PLC). Za potrebe identificiranja parametara za automatsko vođenje neophodno je poznavati fizikalna zbivanja (pojave) u cisterni tijekom procesa zagrijavanja. Da bi razvijeni algoritam vođenja bio što vjerodostojniji, dakle da bi što vjernije oslikavao realno stanje, načinjeno-izgrađeno je prototipno postrojenje (cisterna) te razvijen odgovarajući matematički odnosno simulacijski model. Modeliranje procesa zagrijavanja temeljeno je na tzv. energetskom proračunu u kojem su za izvorište podataka korištena fizikalna svojstva mazuta upotrijebljenog tijekom provedbe eksperimenta (Standard-norma GOST 10585-75).

Realan uvid u stanje procesa u cisterni nije bilo moguće vidjeti zbog neprozirnosti mazuta te je odlučeno cisternu opremiti određenim brojem temperaturnih osjetnika kako bi se dobila vremenska i prostorna raspodjela temperature u cisterni tijekom eksperimenta. Nakon provedenih eksperimentalnih istraživanja (mjerenja), rezultati su uspoređeni s odgovarajućim rezultatima teorijskih proračuna. Na temelju izmjerenih vrijednosti temperatura, korištenjem računala, dobivene su izotermne linije po pojedinim presjecima cisterne, a zatim su ti podaci iskorišteni za izračunavanje prostornog temperaturnog polja. Rezultati istraživanja razmatranog problema pokazali su, unatoč načinjenim zanemarenjima u teorijskim razmatranjima, dobru podudarnost eksperimenta i odgovarajućeg teorijskog modela.

Ključne riječi: proces zagrijavanja nafte, vagon cisterna, temperaturno polje, prikupljanje podataka, vizualizacija procesa.